

DECLARATION OF PERFORMANCE


n° CPR_01

1. Unique identification code of the product type:
Dry-pressed ceramic tiles, with water absorption $E_v \leq 0,5 \%$
2. Intended uses: **For internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer:
Ceramiche Supergres Via Statale 467, 34 42013 Casalgrande (RE) - ITALY
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}/A1	EN 14411:2012
Release of dangerous substance (only for GL ceramic tiles):		
- Cadmium	npd	
- Lead	npd	
Breaking strength (thickness $\geq 7,5$)	≥ 1300 N	
Breaking strength (thickness $< 7,5$)	≥ 700 N	
Slipperiness	npd	
Tactility	npd	
Bond strength/adhesion	npd	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

CERAMICHE ATLAS CONCORDE
 Div. SUPERGRES
 (Galli Dr. Marcello)



DECLARATION OF PERFORMANCE

n° UK - CPR_01



1. Unique identification code of the product type:
Dry-pressed ceramic tiles, with water absorption $E_v \leq 0,5 \%$
2. Intended uses: **For internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer:
Ceramiche Supergres Via Statale 467, 34 42013 Casalgrande (RE) - ITALY
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}/A1	BS EN 14411:2012
Release of dangerous substance (only for GL ceramic tiles):		
- Cadmium	npd	
- Lead	npd	
Breaking strength (thickness $\geq 7,5$)	≥ 1300 N	
Breaking strength (thickness $< 7,5$)	≥ 700 N	
Slipperiness	npd	
Tactility	npd	
Bond strength/adhesion	npd	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

CERAMICHE ATLAS CONCORDE

Div. SUPERGRES
 (Galli Dr. Marcello)

DECLARATION OF PERFORMANCE

n° CPR_02

1. Unique identification code of the product type:
Dry-pressed ceramic tiles, with water absorption $E_v \geq 10\%$
2. Intended uses: **for internal walls**
3. Name or registered trade mark, and contact address of the manufacturer:
Ceramiche Supergres Via Statale 467, 34 42013 Casalgrande (RE) - ITALY
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performances


Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14411:2012
Release of dangerous substance:		
- Cadmium	npd	
- Lead	npd	
Adhésif à base de ciment (type C2 – EN 12004)	$\geq 1,0N/mm^2$	
Thermal shock resistance	Pass	
Durability for internal use	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Casalgrande 11/11/2022

CERAMICHE ATLAS CONCORDE

Div. SUPERGRES
 (Galli Dr. Marcello)



DECLARATION OF PERFORMANCE

n° UK - CPR_02



1. Unique identification code of the product type:
Dry-pressed ceramic tiles, with water absorption $E_v \geq 10\%$
2. Intended uses: **for internal walls**
3. Name or registered trade mark, and contact address of the manufacturer:
Ceramiche Supergres Via Statale 467, 34 42013 Casalgrande (RE) - ITALY
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	BS EN 14411:2012
Release of dangerous substance:		
- Cadmium	npd	
- Lead	npd	
Adhésif à base de ciment (type C2 – EN 12004)	$\geq 1,0N/mm^2$	
Thermal shock resistance	Pass	
Durability for internal use	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.
 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Casalgrande 11/11/2022

CERAMICHE ATLAS CONCORDE

Div. SUPERGRES
 (Galli Dr. Marcello)